# Assembly Instructions
# Selby Collection Pendant # PSY034

**WARNING: BE SURE TO SHUT OFF POWER AT THE MAIN FUSE OR CIRCUIT BREAKER BOX BEFORE INSTALLING OR SERVICING THIS FIXTURE.**

**NOTE: 1. Before installing, consult local electrical codes for wiring and grounding requirements.**
**2. Read and save these instructions.**

**Contents of Spare Parts:**




1. Thread two screws to the mounting strap, and secure them with two lock nuts. Adjust the length of the screws if necessary.
2. Attach the mounting strap to outlet box by using two mounting screws.
3. Three rods with the length of 9 1/2 " L (x3), are attached in the hardware package, choose the desired installation height you need. Then thread the fixture wires through the rods and threaded pipes as shown in the right graph.
   **The height can be adjustable to 19-1/2 " , 29" or 38-1/2 " by using the rods.**
4. Screw all rods together until securely by using the threaded pipes, then secure the rod assembly to the stem of the socket holder.
5. Pull out the outlet wires and the house grounding wire from the outlet box. Make wire connections using the wire nuts:
   ---The black wire from fixture to the black wire from power source.
   ---The white wire from fixture to the white wire from power source.
   ---Attach the fixture grounding wire to the mounting strap with the green grounding screw. Then connect it to the house grounding wire with the wire nut.
   Carefully put the wires back into the outlet box.
6. Attach the canopy kit to the mounting strap by inserting the screws, and secure it with two ball nuts.
7. Attach the shade onto the socket holder, and then secure it with socket ring.
8. Install a bulb (not included). See relamping label at socket area or packaging for maximum allowed wattage.
9. Turn on the power at the main fuse or circuit breaker box.